# LGNG ATBJE-LI ARTICULATING BOOM LIFT

 Large capacity lithium battery, 100% maintenance-free, smart battery management system, extended battery life. LENIS

- Low noise and zero emission, suitable for urban and indoor construction conditions with requirements for noise reduction and environmental protection.
- Compact size, small tail swing design, convenient for construction tasks in narrow places.
- Efficient AC travel drive system, maintenance-free and offering high levels of safety.
- Intelligent diagnosis system, easy maintenance, reducing operating costs.

## **LGMG Electric - Articulating Boom Lift**

### **SPECIFICATIONS**


MeasurementsMetricUSWork Height Max.15m49'3"Platform Height13m42'8"Horizontal Outreach7.46m24'6"Up and Over Height7.1m23'4"Platform Length1.2m3'11"Platform Width0.9m2'11"Platform Capacity200kg440 lbs© Stowed Length6.7m22'© Overall Width1.5m4'11"© Stowed Height1.98m6'6"© Wheelbase2.03m6'8"© Ground Clearance0.2m8"Productivity355°355°Drive Speed-Stowed5km/h3.1mphDrive Speed-Raised0.8km/h0.5mphGradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3"Turning Radius-Outside4.07m13'4"
Platform Height13m42'8"Horizontal Outreach7.46m24'6"Up and Over Height7.1m23'4"Platform Length1.2m3'11"Platform Width0.9m2'11"Platform Capacity200kg440 lbsI Stowed Length6.7m22'I Overall Width1.5m4'11"I Stowed Height1.98m6'6"I Wheelbase2.03m6'8"I Ground Clearance0.2m8"ProductivityMax. Platform Occupancy2(in)/2(out)Turntable Rotation355°355°Drive Speed-Stowed5km/h3.1mphDrive Speed-Raised0.8km/h0.5mphGradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3"
Horizontal Outreach7.46m24'6"Up and Over Height7.1m23'4"Platform Length1.2m3'11"Platform Width0.9m2'11"Platform Capacity200kg440 lbsI Stowed Length6.7m22'I Overall Width1.5m4'11"I Stowed Height1.98m6'6"I Wheelbase2.03m6'8"I Ground Clearance0.2m8"ProductivityMax. Platform Occupancy2(in) / 2(out)Turntable Rotation355°355°Drive Speed-Stowed5km/h3.1mphDrive Speed-Raised0.8km/h0.5mphGradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3"
Up and Over Height7.1m23'4"Platform Length1.2m3'11"Platform Length0.9m2'11"Platform Capacity200kg440 lbsI Stowed Length6.7m22'I Overall Width1.5m4'11"I Stowed Height1.98m6'6"I Wheelbase2.03m6'8"I Ground Clearance0.2m8"ProductivityMax. Platform Occupancy2(in) / 2(out)Turntable Rotation355°355°Drive Speed-Stowed5km/h3.1mphDrive Speed-Raised0.8km/h0.5mphGradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3"
Platform Length1.2m3'11"Platform Width0.9m2'11"Platform Capacity200kg440 lbsImage: Stowed Length6.7m22'Image: Stowed Length6.7m22'Image: Stowed Length1.5m4'11"Image: Stowed Height1.98m6'6"Image: Stowed Height1.98m6'6"Image: Stowed Height1.98m6'6"Image: Stowed Height1.98m6'8"Image: Stowed Height1.98m6'8"Image: Stowed Height1.98m6'8"Image: Stowed Height1.98m6'8"Image: Stowed Height1.98m6'8"Image: Stowed Height1.98m6'8"Image: Stowed Clearance0.2m8"Image: Stowed Clearance0.2m8"Image: Stowed Clearance355°355°Image: Stowed Stowed355m355°Image: Stowed Stowed5km/h3.1mphImage: Stowed Stowed30%30%Image: Stowed Stowed12.5m/s28mphImage: Stowed Stowed Stowed2.2m7'3"
Platform Width0.9m2'11"Platform Capacity200kg440 lbsImage: Stowed Length6.7m22'Image: Overall Width1.5m4'11"Image: Stowed Height1.98m6'6"Image: Wheelbase2.03m6'8"Image: Stowed Clearance0.2m8"ProductivityMax. Platform Occupancy2(in) / 2(out)Turntable Rotation355°355°Drive Speed-Stowed5km/h3.1mphDrive Speed-Raised0.8km/h0.5mphGradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3"
Platform Capacity200kg440 lbsImage: Stowed Length6.7m22'Image: Overall Width1.5m4'11"Image: Stowed Height1.98m6'6"Image: Stowed Height1.98m6'6"Image: Stowed Height1.98m6'8"Image: Stowed Height1.98m6'8"Image: Stowed Height0.2m8"Image: Stowed Clearance0.2m8"Image: Productivity355°355°Image: Stowed Clearance5km/h3.1mphImage: Stowed Clearance0.8km/h0.5mphImage: Stowed Clearance0.8km/h0.5mphImage: Stowed Clearance0.8km/h30%Image: Stowed Clearance30%30%Image: Stowed Clearance12.5m/s28mphImage: Stowed Clearance2.2m7'3"
Image: Constraint of the constra
Image: Overall Width1.5m4'11''Image: Stowed Height1.98m6'6''Image: Wheelbase2.03m6'8''Image: Orego Wheelbase0.2m8''Image: Orego Wheelbase0.2m8''Image: Orego Wheelbase0.2m8''Image: Orego Wheelbase0.2m8''Image: Orego Wheelbase0.2m8''Image: Orego Wheelbase0.2m8''Image: Orego Wheelbase355°355°Image: Orego Wheelbase355°355°Image: Orego Wheelbase5km/h3.1mphImage: Orego Wheelbase0.8km/h0.5mphImage: Orego Wheelbase30%30%Image: Orego Wheelbase12.5m/s28mphImage: Orego Wheelbase2.2m7'3''
Image: Stowed Height1.98m6'6''Image: Wheelbase2.03m6'8''Image: Ground Clearance0.2m8''Image: Productivity3''8''Max. Platform Occupancy2(in) / 2(out)Turntable Rotation355°355°Drive Speed-Stowed5km/h3.1mphDrive Speed-Raised0.8km/h0.5mphGradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3''
Image: Constraint of Constr
GradeabilityDiscriminationGradeability0.2mMax. Platform Occupancy2(in) / 2(out)Turntable Rotation355°Drive Speed-Stowed5km/hDrive Speed-Raised0.8km/hOradeability30%Max. Wind Speed12.5m/sTurning Radius-Inside2.2mTurning Radius-Inside2.2m
ProductivityMax. Platform Occupancy2(in) / 2(out)Turntable Rotation355°Drive Speed-Stowed5km/hDrive Speed-Raised0.8km/hOradeability30%Max. Wind Speed12.5m/sTurning Radius-Inside2.2m
Max. Platform Occupancy2(in) / 2(out)Turntable Rotation355°355°Drive Speed-Stowed5km/h3.1mphDrive Speed-Raised0.8km/h0.5mphGradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3''
Turntable Rotation355°355°Drive Speed-Stowed5km/h3.1mphDrive Speed-Raised0.8km/h0.5mphGradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3"
Drive Speed-Stowed5km/h3.1mphDrive Speed-Raised0.8km/h0.5mphGradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3"
Drive Speed-Raised0.8km/h0.5mphGradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3"
Gradeability30%30%Max. Wind Speed12.5m/s28mphTurning Radius-Inside2.2m7'3"
Max. Wind Speed   12.5m/s   28mph     Turning Radius-Inside   2.2m   7'3"
Turning Radius-Inside 2.2m 7'3"
Turning Radius-Outside 4.07m 13'4"
Max.Slope 3°/3° 3°/3°
Tires Type Solid Non-marking
Tires Size       600x190mm       1'11"x7"
Power
Power Source 48V 250Ah
Hydraulic System
Hydraulic Oil Volume 25L 6.6gal
Weight
Machine Weight (CE/ANSI) 6950kg 15322 lbs

STANDARD FEATURES		
Proportional control	Over tilt protection system	
Horn	Overload sensing system	
AC drive motor	Intelligent diagnostic system	
GPS connector	Anti-entrapment protection	
Power switch	Auto-leveling platform	
Drop bar entry	Solid non-marking tires	
Descent alarm with flashing beacon		

-


OPTIONAL	
AC power to platform	Platform
Platform tool box	Platform


Telematics



work light

swing gate





A13JE-Li Working Range 4m 2m 0 STD-1 2m **M** 4m -2m 0 2m 4m 6m 8m

Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only. This brochure comes into effect in February, 2023.

#### LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China Email: sales@lgmg.com.cn Tel: +86 531 6787 9283

#### LGMG Europe B.V.

Address: Donker Duyvisweg 301, 3316 BL Dordrecht, The Netherlands Email: sales@lgmgeurope.com Tel: +31 850 642 777

#### LGMG North America Inc.

Address: 1445 Sheffler Dr, Chambersburg, PA. 17201, USA Email: sales@lgmgna.com Tel: +1 833 288 5464

www.lgmglifts.com

